

Testing and Conformity Statement

The development of **Fireply X®** has moved beyond simply supplying a fire-retardant board. The pursuit of perforated and prefinished solutions, certified as **Fire Hazard Group 2**, has resulted in testing being based on a system, not just the board alone. The certification of this product relies on each piece of the system being managed to ensure conformity to the rigorous and stringent Australian Standards.

Don't fear, this is a good thing! We have done all the research, development and testing to ensure we can supply a range of products that are not only natural, unique and beautiful, but also easy to specify, easy to install and most importantly – compliant!

When specifying a system, there is potential for products, or in this case, parts of the system to be substituted. In this event, while potentially saving a few dollars, there is a risk the finished works won't be complaint (or safe) therefore jeopardising the safety and performance of the product.

For this reason, we have made the decision to not make our testing certificate, regulatory information report (RIR) and testing assessment publicly available. With these documents readily available there poses a significant risk that aspects of the system may be altered, intentionally or otherwise, while the certificate and reports are still used to 'certify' the finished works. For this reason, we aim to work as closely as possible with those working intricately with the design, installation and certification of the project. We will gladly provide the certificate and RIR in confidence when required by these individuals and companies for specific projects.

We confirm with this statement, that the **Fireply X®** product, when used in specific systems, is certified to Fire Hazard Group 2 in accordance with AS 5637.1:2015 using ISO 9705-2003 (room burn test) as the test method. This includes a range of perforated options, all available in a range of pre-finished stains and lacquers, with a range of thicknesses, fixing methods, void depths and with the option of express joints up to 10mm.

This statement does not replace the need to supply a certificate or RIR, or guarantee the suitability of this product for your specific project or application.

| | |
|-------------------------------------|---------------------------------------|
| Report Number: FAS200450 | Issue Date: 26 February, 2021 |
| Test Date: 23 November, 2020 | Expiry Date: 28 February, 2026 |

We are happy to answer questions, provide guidance and assist in determining if **Fireply X®** is the solution for your design challenges. Please contact us if require more information or further documentation.

Yours sincerely



Craig Graham
Co-General Manager
Operations, Panels & Brand



Anthony Wardrop
Co-General Manager
Resource, Production & Sales

For more information from our expert team on our natural, unique and beautiful timber veneers of exceptional quality:

VISIT
matildaveneer.com.au
EMAIL
hello@matildaveneer.com.au
CALL
+ 61 7 5594 0655

   /matildaveneer
matildaveneer.com.au