

# Fireply X<sup>®</sup> – LRV Testing

## Statement of Performance

### What is LRV Testing?

Luminance Reflectance Value (LRV) is a measurement of the amount of light reflected by a surface. LRV testing is important to certify contrast between materials, such as doors and walls, or floors and tactile indicators (TGSi), to assist the vision impaired.

### LRV Test Results

The following are the test results of the tristimulus value Y (LRV):

Fireply X <sup>®</sup> Prefinished FR Plywood (Group 2) Finish	Mean Dry LRV (Yd)
Ash	51.07
Natural	35.89
Blackbutt	31.33
Spotted Gum	14.00
Ironbark	9.02
Aged	6.78
Jarrah	4.93
Ebony	3.55

Report Number: EG-231019-LL

Issue Date: 11 July, 2023

### Technical Reference

The associated report references the following:


- Appendix B of Australian Standard (AS) 1428.1-2009 'Design for access and mobility, Part 1: General requirements for access – New building work' (**AS 1428.1**)
- Appendix E of Australian Standard AS/NZS 1428.4.1-2009 'Design for access and mobility, Part 4.1: Means to assist the orientation of people with vision impairment— Tactile ground surface indicators' (**AS/NZS 1428.4.1**)

We are happy to answer questions, provide guidance and assist in determining if **Fireply X<sup>®</sup>** is the solution for your design challenges. Please contact us if require more information or further documentation.

Yours sincerely



**Craig Graham**  
Co-General Manager  
Operations, Panels & Brand



**Anthony Wardrop**  
Co-General Manager  
Resource, Production & Sales

For more information from our expert team on our natural, unique and beautiful timber veneers of exceptional quality:

**VISIT**  
[matildaveneer.com.au](http://matildaveneer.com.au)  
**EMAIL**  
[hello@matildaveneer.com.au](mailto:hello@matildaveneer.com.au)  
**CALL**  
+ 61 7 5594 0655

   /matildaveneer  
[matildaveneer.com.au](http://matildaveneer.com.au)